

# PROFITEC



PASSION MEETS DESIGN

**COFFEE IS  
A KIND  
OF MAGIC  
YOU CAN  
DRINK**

# PROFITEC

Profitec GmbH was founded in 1985 and has specialized in the sale of Italian espresso machines and technical products from the beginning. We have developed and manufactured hand-made, high-end semi-automatic espresso machines since the 1990's. Now we have decided to use our know-how to build our own espresso machines and market them under our own brand.

Passion meets design.



GO



# GO

## SINGLE BOILER WITH RING BREW GROUP

### Compact and fast


The GO is a compact single-boiler espresso machine with a ring brew group.

1,2, 3...GO: After a very short heating phase, the machine is ready to make your espresso.

Press & GO: The espresso extraction, the steam mode activation and switching the machine on and off, simply at the touch of a button.

Never lose Control: The display shows the coffee brewing time to the second. The PID temperature control also allows you to set the desired temperature for coffee extraction and steam. The brewing pressure can be adjusted on the easily accessible expansion valve. In addition, a reminder can be set to display when to clean it if you wish. The ECO mode also allows you to program a timer to switch off the boiler when not in use to save energy.

YOUR TASTE. YOUR STYLE. YOUR MACHINE - Which GO is yours?



- Item No. CM500001-00
- Item No. CM500001-01
- Item No. CM500001-02
- Item No. CM500001-03
- Item No. CM500001-04

- Single boiler with ring brew group
- PID for setting the brew boiler temperature
- Display for precise shot timer (second-by-second)
- Fast Heat-Up mode
- Programmable ECO mode
- Reminder function for brew group cleaning
- Brass boiler - 0.3 l
- Boiler insulation
- Expansion valve for adjusting brew pressure
- Vibration pump
- Pump pressure gauge
- Control buttons
- Steam valve
- Water tank with 2.8 l capacity and water tank adapter

### \* EXCLUSIVE LINE:

Available exclusively through our EXCLUSIVE LINE dealers. Please check with your local specialist dealer for more information.

# PRO 300



# PRO 300


## DUAL-BOILER WITH PID CONTROL

### Fast and adaptable

The PRO 300 is a dual boiler portafilter machine with a ring brew group.

Depending on your needs, it can be used as a single boiler machine. The Fast Heat-Up Mode allows it to be ready for espresso preparation in approximately 7 minutes. The stainless-steel steam and hot water boiler can be turned on and off as needed.

The PID display allows you to adjust the coffee boiler temperature to your preference. Additionally, the display shows the brewing time for coffee and espresso with second-by-second precision.



■ Item No. CM500002-01

■ Art.-Nr. Pro300

- 
- Dual boiler (optional use as a single boiler)
  - Ring brew group with 0.3 L brass boiler
  - PID for adjusting coffee boiler temperature
  - Display with precise shot timer
  - Fast Heat-Up Mode
  - Programmable ECO mode
  - Stainless steel boiler with 0.75 L capacity for steam and hot water
  - Vibration pump
  - Boiler pressure gauge
  - Water tank with 2.8 l capacity and water tank adapter
  - Automatic shut-off with sensor in case of water shortage

**MOVE**





# MOVE

## DUAL BOILER WITH OLED DISPLAY

### Small and versatile


The MOVE is an exclusive dual boiler portafilter machine with an optimized ring brew group, ready for use in about 9 minutes.

The shot buttons can be individually programmed, and the sleek OLED display provides a clear overview of all functions. The display buttons allow for a variety of settings, including automatic on/off times. The stainless-steel steam and hot water boiler can be switched on or off as needed, allowing the MOVE to be used as either a single boiler or dual boiler machine, depending on your needs.

The "Barista Light" adds a special touch to the extraction process, and you can choose to have it on all the time or only during extraction. The MOVE comes with a bottomless filter holder featuring a silicone attachment and three different cup filters, making it versatile and space-saving. Its compact design is paired with hassle-free maintenance, thanks to the automatic brewing group cleaning function.

Looking for something more exclusive? The MOVE comes with handcrafted American walnut handles, adding a touch of elegance.

In 2025 because the MOVE will be available in three new vibrant colors.



■ Item No. CM50003-00

- Dual boiler (optional use as a single boiler)
- Optimized ring brew group with 0.4 L brass boiler
- Sleek OLED display
- Programmable shot buttons (by time)
- Timer function
- Adjustable pre-infusion
- Fast Heat-Up mode
- Automatic brew group cleaning
- Programmable ECO mode
- Barista Light
- Stainless steel boiler with 0.75 l capacity for steam and hot water
- Portafilter with silicone grip
- Low-noise vibration pump
- Dual pressure gauges for boiler and pump pressure
- Water tank with 2.8 L capacity and water tank adapter
- Automatic shut-off with sensor in case of water shortage

### \* EXCLUSIVE LINE:

Available exclusively through our EXCLUSIVE LINE dealers. Please check with your local specialist dealer for more information.

# PRO 400



# PRO 400

## HEAT EXCHANGER MACHINE WITH MULTIFUNCTION SWITCH

### Compact and customizable

The PRO 400 is a compact heat exchanger machine with a striking design. The included different colored valve disclets allow you to change the look of the machine in no time.

Technically, the PRO 400 is an espresso machine in a class of its own. A convenience switch underneath the machine allows three preset temperatures to be easily chosen and to activate or deactivate the preinfusion and the ECO mode.

The stylish dual gauge allows the boiler and pump pressure to be kept an eye on at all times, allowing the brewing pressure to be easily determined and changed when necessary.



Item No. CM500004-00

- 
- Heat exchanger system
  - Profitec brew group with stainless steel bell
  - Multifunction switch
    - Three selectable temperatures (120° C, 124° C, 128° C)
    - Preinfusion ON/OFF
    - ECO mode ON/OFF
  - Adjustable expansion valve
  - Dual pressure gauge for boiler and pump pressure
  - 1.6 l stainless steel boiler
  - Stainless steel heating element
  - Vibration pump
  - Water tank with approximately 2.8 l capacity and water tank adapter
  - Automatic shut-off with sensor in case of water shortage
  - Durable rotary valves
  - High-quality steam and hot water wands
  - Removable cup tray
  - Blind filter holder under the drip tray interchangeable colored valve discs included

# JUMP



# JUMP


## HEAT EXCHANGER MACHINE WITH DISPLAY AND MULTIFUNCTION SWITCH

### Compact and exclusive

The JUMP is a compact and powerful heat exchanger machine that has a small footprint.

A convenient switch located underneath the machine allows for easy selection of three preset temperatures, as well as activation or deactivation of the preinfusion and ECO mode. The discreet display not only lets you monitor the selected settings but also shows the duration of the espresso extraction (shot counter) and alerts you when the water tank is empty.

With its black rail, brushed front and handcrafted American walnut handles, the JUMP has an exclusive look.



Item No. CM500005-00

- Heat exchanger system
- Profitec brew group with stainless steel bell
- Multifunction switch
  - Three selectable temperatures (120°C, 124°C, 128°C)
  - Preinfusion ON/OFF
  - ECO mode ON/OFF
- Display to show:
  - Shot counter
  - Preinfusion ON/OFF
  - ECO mode ON/OFF
  - Temperature unit
  - Empty water tank
- 1.6 l stainless steel boiler
- Joystick valves
- Handles made of American walnut
- Dual gauge for boiler and pump pressure
- Low-Noise Vibration pump
- 2.8 l water tank with built-in adapter
- Automatic low water volume shut-off
- Removable cup tray

\* **EXCLUSIVE LINE:**

Available exclusively through our EXCLUSIVE LINE dealers. Please check with your local specialist dealer for more information.

# RIDE



# RIDE

## DUAL BOILER WITH PID CONTROL


### Modern look, flexible handling

The RIDE is characterized by the fact that both the coffee and steam boilers are heated simultaneously. This allows the steam temperature to be reached much faster, ensuring a more stable steam performance during espresso extraction. Optionally, the RIDE can also be used as a single-boiler machine.

With the Fast Heat-Up mode activated, the machine is ready to use much faster. Regardless, the temperatures of both boilers can be individually adjusted via the PID control. The RIDE also offers you the option of programming automatic switch-on and switch-off times and much more. These settings are displayed on the subtle screen, along with the shot timer.

The modular, bottomless portafilter can be quickly and easily converted with silicone attachments (1 spout and 2 spouts). This not only saves space but also allows for easy and hygienic cleaning.

And then there's the look: The elegant anthracite-colored side panels stand out in contrast to the satin-finished front, the cup tray, and the silver drip tray. The pressure gauges harmonize with the display and round off the appearance.



Item No. CM500013-00

- 
- Dual boiler (single boiler option)
  - Profitec brew group with stainless steel mushroom
  - Simultaneous heating of both boilers
  - PID control for individual temperature adjustment of both boilers
  - Programmable Fast Heat-UP Mode
  - Programmable on and off times
  - Programmable ECO mode
  - Active & passive preinfusion mode
  - Reminder function for brew group cleaning
  - Reminder function for filter change
  - Discreet Display
  - Shot counter
  - Joystick valves
  - Vibration pump
  - 2.8 l Water tank with built-in adapter
  - 0.75 l stainless steel coffee boiler
  - 1.0 l stainless steel steam and hot water boiler
  - Boiler and pump pressure gauges
  - Expansion valve for individual adjustment of the brewing pressure

# DRIVE





# DRIVE

## DUAL BOILER

### WITH FLOW CONTROL AND ROTARY PUMP


#### Intelligent and comfortable

The DRIVE offers you maximum performance and convenience:

To get your machine up and running faster, you can activate the Fast Heat-Up Mode. Regardless of this, you have the option to program automatic switch-on and switch-off times.

The built-in Flow Control valve allows you to regulate the water flow to the brew group and also to change it during brewing (Flow Control). Various settings are available for in active and passive pre-infusion modes to achieve the best possible extraction result. The integrated PID control allows individual temperature settings for both boilers. The discreet OLED display not only shows you the espresso's flow time to the second, but also provides you with a wealth of information. In addition, you have the option of making a variety of settings.

Depending on your needs, you can choose between water tank and fixed water connection modes and switch the steam boiler on or off as needed.



Item No. CM500009-00

- 
- Dual boiler (single boiler option)
  - Profitec brew group with stainless steel mushroom
  - Built-in flow profile valve with eye-catching pressure gauge
  - PID control for independent temperature adjustment of both boilers
  - OLED Display
  - Display indicates the brewing time in seconds
  - Programmable ECO mode
  - Reminder function for brew group cleaning
  - Reminder function for filter change
  - Rotary pump
  - Joystick valves
  - Large boiler and pump pressure gauges in classic black
  - 0.75 l stainless steel coffee boiler
  - Switchable from water tank to fixed water connection
  - 2.8 l water tank with built-in adapter
  - Automatic shut-off when machine reaches low water volume in water tank operation
  - Separate grid to raise cups

# PRO 800



# PRO 800

## HAND LEVER DIPPING SYSTEM WITH PID CONTROL

### Nostalgic and classic style

The new version of our PRO 800 hand-lever machine has a stylish, elegant look. The PRO 800 makes the hearts of connoisseurs and hand-lever espresso machines enthusiasts beat faster.

The new Pro 800 comes with lever valves for steam and hot water. The handles of the lever valves, as well as the handle of the hand lever and the portafilter, have been handcrafted from the noble wood of the American walnut tree.

While the large, pine-green pressure gauge, another visual highlight, blends perfectly into the classic design, the PID is discreetly hidden behind the water collection tray.

Get the best possible espresso due to the pre-infusion provided by the massive brew group and the special pressure process.



Item No. CM500012-00

- Dipper (one-circuit) system
- Heavy duty lever brew group [7.8 kg]
- Practical lever valves for steam and hot water extraction
- PID control for regulating the boiler temperature
- Programmable ECO Mode
- Vibration pump is only activated when using the water tank
- Vibration pump is not activated when using a fixed water connection
- 3.5 l copper boiler
- Switchable from water tank to a fixed water connection
- Drip tray with approx. 1.25 l capacity
- Connection to water drainage is possible
- 2.8 l water tank with built-in adapter
- High quality steam and hot water pipes
- Large boiler pressure gauge
- Large removable cup tray
- Additional bottomless portafilter

# PRO M54



# PRO M54

## HIGH PERFORMING GRINDER WITH A COMPACT MINIMALIST DESIGN

### **Sleek and compact**

The Pro M54 is a powerful on-demand grinder with steel burrs (ø 54 mm) and manual grinding function. Eight grams of fresh coffee can be grinded into your portafilter in just ten seconds.

Due to its minimalist and compact design, the Pro M54, fits perfectly in today's small and modern kitchen.



■ Item No. 20200

■ Item No. 20275

- 
- ø 54 mm steel burrs
  - Easy to dial-in grinder, with small steps
  - Grinder corpus made of aluminium
  - Compact size design that any kitchen can accommodate
  - Housing made of high quality stainless steel
  - Removable spout that allows for easy cleaning
  - 250 g bean hopper
  - Catching tray for the grounds

# TWIST A54



# TWIST A54

## COMPACT GRINDER

### WITH TIMER PROGRAMMING

#### **Customizable and compact**

This grinder offers versatile programming options, including three preset portion quantities: Single Shot, Double Shot, and Single Dose. In addition, the TWIST A54 also offers three different operating modes: Select mode, Barista mode, Single Dose mode. Customization is at your fingertips.

Featuring a 54mm steel grinding burrs for consistent results, the TWIST A54's grinding degree can be easily adjusted.

Experience the perfect balance of performance and aesthetics with the TWIST A54's branded front panel creating a contrast against the sleek matt black housing.



Item No. GR500004-00

- 
- Three programmable dose sizes:  
Single Shot / Double Shot / Single Dose
  - Three selectable operating modes:  
Select Mode / Barista Mode / Single Dose Mode
  - Adjustable portafilter holder
  - Stepless grind size adjustment
  - ø 54 mm steel burrs
  - Aluminum grinder mechanism
  - Compact design
  - Matte black housing
  - Bean hopper capacity: 250 g
  - Coffee grounds tray included
  - RPM: 1400 RPM
  - Grinding cycle: T-On: 10 sec, T-Off: 80 sec

# TWIST SD54





# TWIST SD54

## SINGLE-DOSE GRINDER

### FOR HIGH DEMANDS AND LOW RETENTION

#### Flexible and precise

The TWIST SD54 enables precise, reproducible grinding results of the highest quality. The Single Dosing brings the freshest grind into the portafilter, without loss of aromas and ground coffee.

Simply weigh the beans in the Dosing Cup, pour them into the Coffee Bellow, close the lid and place the Dosing Cup back on the integrated leveler. The magnet on the Dosing Cup ensures that it remains stable and cannot tip over. After the grinding process, a few pulses on the Coffee Bellow ensure that the coffee particles remaining in the grinding chamber are released. Place the portafilter on the dosing cup, turn it over and use the leveler to distribute the ground coffee evenly. All that's left to do is to tamp, brew and enjoy.

The steel burrs have a diameter of 54 mm and the degree of grinding is infinitely adjustable.



Item No. GR500005-00

- Coffee Bellow
- Dosing Cup
- Integrated stainless steel Leveler
- Stepless grind size adjustment
- ø 54 mm steel burrs

- Aluminum grinder mechanism
- Compact design
- Housing: stainless steel, black powder-coated
- RPM: 1400 RPM
- Grinding cycle: T-On: 10 sec, T-Off: 80 sec

# PRO T64



# PRO T64

## ON-DEMAND GRINDER WITH DIGITAL PROGRAMMING

### **Straightforward and direct**

The Pro T64 is a professional grinder with a direct grinding function and a programmable grind time to a 10th of a second. Handling is easy and simple: Insert the porta filter, press the portioning button, done.

The straight-forward, simple industrial look of the high-end, stainless steel housing with side panels made of Plexiglas is perfectly complemented by the tinted bean hopper.



Item No. GR500002-00

- 
- 64 mm steel burrs
  - Timer for individual programming of grinding duration, with integrated shot counter
  - Display for grind time indication
  - Two buttons for automatic coffee dispensing, with optional manual dispensing available
  - Fast grinding:
    - Single Shot: approx. 3.8 sec  $\pm$  0.2 sec –  $\approx$  7 - 9 g
    - Double Shot: approx. 5.4 sec  $\pm$  0.2 sec –  $\approx$  14 - 16 g
  - Stepless grind size adjustment
  - Aluminum grinder mechanism
  - Adjustable holder for securing the portafilter: hands-free operation possible
  - Tinted bean hopper with 500 g capacity
  - Catch tray for coffee grounds

# PRODUCT OVERVIEW



## GO

- CM500001-00
- CM500001-01
- CM500001-02
- CM500001-03
- CM500001-04



## PRO 300

- Pro300
- CM500002-01



## MOVE

- CM500003-00



## PRO 400

- CM500004-00

## ESPRESSO MACHINES

Item No.

System	Single boiler	Dual boiler*	Dual boiler*	Heat exchanger
Brew group	Ring brew group	Ring brew group	Optimized Ring brew group	Profitec brew group
Pump	Vibration	Vibration	Vibration „Low-Noise“	Vibration
Fast Heat-Up mode	•	•	•	
PID control	•	•	•	•
Shot Counter	•	•	•	
Timer-Function			•	
Valves	Rotary	Rotary	Joystick	Rotary
Steam (1) / hot water (2)	1	1 + 2	1 + 2	1 + 2
Water tank	2,8 l	2,8 l	2,8 l	2,8 l
Switchable water tank / fixed water supply				
Automatic water shortage shut-off		•	•	•
Boiler material	Brass	Brass/Stainless steel	Brass/Stainless steel	Stainless steel
Boiler volume (coffee/steam and hot water)	0,3 l	0,3/0,75 l	0,4 l/0,75 l	1,6 l
Boiler pressure gauge		•	•	•
Pump pressure gauge	•		•	•
Adjustable brewing pressure	•			•
Number of portafilters	1	2	1**	2
Power usage EU, UK, CH, AU (230 V)	1500 W	2300 W	2300 W	1500 W
Power usage US, JP (115 V)	1500 W	1700 W	1700 W	1500 W
Weight	12,9 kg	18 kg	18,7 kg	21,5 kg
Dimensions without portafilter (W x D x H)	210 x 362 x 381	255 x 415 x 385	270 x 445 x 375	228 x 448 x 372
Dimensions with portafilter (W x D x H)	210 x 410 x 381	255 x 475 x 385	270 x 475 x 375	228 x 558 x 372

\* Switchable on/off steam boiler

\*\* "Modular" with silicone attachment

\*\*\* Lever height

# PRODUCT OVERVIEW



**JUMP**

CM500005-00



**RIDE**

CM500013-00



**DRIVE**

CM500009-00



**PRO 800**

CM500012-00

## ESPRESSO MACHINES

Item No.

System	Heat exchanger	Dualboiler*	Dual boiler*	Dipper (one-circuit)
Brew group	Profitec brew group	Profitec Brühgruppe	Profitec brew group	Hand lever
Pump	Vibration „Low-Noise“	Vibration	Rotary	Vibration
Fast Heat-Up mode		•	•	
PID control	•	•	•	•
Shot Counter	•	•	•	
Timer-Function		•	•	
Valves	Joystick	Joystick	Joystick	Joystick
Steam [1] / hot water [2]	1 + 2	1 + 2	1 + 2	1 + 2
Water tank	2,8 l	2,8 l	2,8 l	2,8 l
Switchable water tank / fixed water supply			•	•
Automatic water shortage shut-off	•	•	•	•
Boiler material	Stainless steel	Stainless steel	Stainless steel	Copper
Boiler volume (coffee/steam and hot water)	1,6 l	0,75 / 1,0 l	0,75 / 2,0 l	3,5 l
Boiler pressure gauge	•	•	•	•
Pump pressure gauge	•	•	•	
Adjustable brewing pressure	•	•	•	
Number of portafilters	2	1**	2	3
Power usage EU, UK, CH, AU (230 V)	1500 W	2100 W	1600 W	1700 W
Power usage US, JP (115 V)	1500 W	1700 W	1600 W	1600 W
Weight	21,5 kg	28 kg	31 kg	35,5 kg
Dimensions without portafilter (W x D x H)	302 x 447 x 393	300 x 450 x 370	340 x 485 x 420	339 x 505 x 492
Dimensions with portafilter (W x D x H)	302 x 555 x 393	300 x 560 x 370	340 x 580 x 420	339 x 593 x 740***

\* Switchable on/off steam boiler

\*\* "Modular" with silicone attachment

\*\*\* Lever height

# PRODUCT OVERVIEW



## GRINDERS

### PRO M54

### TWIST A54

### TWIST SD54

### PRO T64

Item No.	<span style="display: inline-block; width: 10px; height: 10px; background-color: black; margin-right: 5px;"></span> 20275 <span style="display: inline-block; width: 10px; height: 10px; background-color: gray; margin-right: 5px;"></span> 20200	GR500004-00	GR500005-00	GR500002-00
Grinder corpus	Aluminium	Aluminium	Aluminium	Aluminium
Burr diameter	54 mm	54 mm	54 mm	64 mm
Burr material	Steel	Steel	Steel	Steel
Motor performance	235 W	235 W	235 W	450 W
Bean hopper capacity	250 g	250 g		500 g
Dosing option	Manual	Programmable	Manual	Programmable
Grind setting	Graduate	Stepless	Stepless	Stepless
Weight	5.1 kg	5.26 kg	7 kg*	7.5 kg
Frequency EU, UK, CH, AU (230 V)	50 Hz	50 Hz	50 Hz	50 Hz
Frequency US (115 V)	60 Hz	60 Hz	60 Hz	60 Hz
Dimensions ( W x D x H)	115 x 175 x 355 mm	130 x 170 x 357 mm	120 x 225 x 345 mm	170 x 250 x 430 mm

\* incl. Coffee Bellow, Dosing Cup und Leveler

PROFITEC - SINCE 1985  
- HANDMADE -

**Profitec GmbH**

Industriestr. 57-61

69245 Bammental

Telefon: +49 (0) 6223 9205-0

[www.profitec-espresso.com](http://www.profitec-espresso.com)